

EGGSHELL

A solvent-borne highly durable, washable eggshell finish for interior use only. It offers outstanding resistance to steam and condensation. Especially suitable for high traffic areas e.g. schools, hospitals, kitchens and bathrooms.

AVAILABILITY

Colour Range Refer to current Crown Trade Literature.

Packaging 1, 2.5 and 5 litre.

PROPERTIES

Drying Time Under normal drying conditions touch dry in 4-6 hours and recoatable after 16 hours. Allow for adequate ventilation during the drying period. A characteristic of the new technology used in this product is that whiteness intensifies as the paint dries. The sheen will reach its final level approximately 2 weeks after application.

Finish Eggshell.

Composition Pigment: Titanium Dioxide, coloured pigments and extenders.
Resin: Thixotropic alkyd. Alkyd.
Solvent: Dearomatised White Spirit.

Spreading Rate Up to 16m² per litre depending on surface texture.

Wet Film Thickness 62.5 micrometres at 16m² per litre

Dry Film Thickness 30 micrometres at 16m² per litre.

Volume Solids 48% Brilliant White other colours will vary.

Flash Point 40°C (closed cup).

VOC Content EU limit value for this product (cat.A/d): 300 g/l (2010). This product contains max. 299 g/l VOC.

Limitations For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New Surfaces All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Prime all surfaces including powdery, polished plaster or dense surfaces with Crown Trade Alkali Resisting Sealer.

Previously decorated surfaces All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects with Sandtex Trade Ready Mixed Filler. Patch prime bare and filled areas with Crown Trade Alkali Resisting Sealer. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Crown Trade Alkali Resisting Sealer. Bring forward patch primed areas with one coat of Crown Trade Eggshell.

COATING SYSTEM Apply one or two coats as required. Certain colours may require additional coats to give complete obliteration.

APPLICATION Stir well before use. Apply by brush or medium pile roller. Always intermix packs for colour consistency. Please check for colour accuracy prior to application. Crown Paints is not liable for

decorating costs caused as a result of an incorrect colour being applied. Always intermix packs for colour consistency. Please check for colour accuracy prior to application. Crown Paints is not liable for decorating costs caused as a result of an incorrect colour being applied. NOTE: Our products are formulated to the highest quality, however recent changes made to meet the reduced solvent levels required by current legislation may in certain circumstances, such as lack of daylight, lead to white and very pale colours yellowing over time.

CLEANING

Return surplus material to container. Clean with a proprietary cleaner immediately after use.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions between 5°C and 40°C and inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information. For help or more information contact the Crown Trade Customer Relations Team on:

Tel: 0330 0240297

Fax: 0330 0240278

e-mail: info@crowntrade.co.uk

website: www.crowntrade.co.uk

This information is correct at date of issue June 2015.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Tel: 01254 704951 Fax: 01254 870155

Email: info@crowntrade.co.uk

Website: www.crowntrade.co.uk