



Dulux Trade Evolve Matt

Dulux Trade Evolve Matt is a professional quality, high opacity emulsion made with 35% recycled paint content. **Dulux Trade Evolve Matt** has a smooth flow for easy application and offers excellent coverage with a high quality finish. Suitable for all normal interior wall and ceiling surfaces.

KEY BENEFITS

- Made with minimum 35% recycled paint content
- Excellent Application and Finish
- High Opacity
- Coverage up to 17m² Per Litre

PRODUCT INFORMATION

Typical Use

Suitable for interior use on all normal interior wall and ceiling surfaces. For interior areas that are likely to suffer from mould growth, use **Mouldshield** Fungicidal Eggshell* from **Dulux Trade**.

Pack Size

5L

Colour Range

White Only

Film Properties

Chemical Resistance: Not suitable.

Heat Resistance: Not suitable for use on heated surfaces, such as radiators.

Water Resistance: Where frequent heavy condensation is likely, as in some kitchens and bathrooms, **Dulux Trade Diamond Eggshell** is more suitable.

Composition (nominal)

Binder: Copolymer Emulsion.

Solvent: Water.

Volume Solids

Solid content by volume: 31% (nominal)

SURFACE PREPARATION

To get the best results with **Dulux Trade Evolve Matt**, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux Trade Evolve Matt** (up to 1 part clean water to 5 parts paint). The normal finishing process is 2 full



Dulux Trade Evolve Matt

coats of **Dulux Trade Evolve Matt**, but on previously painted surfaces in good condition where similar colours are used, 1 coat may be sufficient.

APPLICATION METHOD

Brush, roller, conventional spray or airless spray.

As with other water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 17m² per litre.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint.

Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.

Conventional spray application: Add up to 1 part clean water to 2.5 parts paint.

Airless spray application: Add up to 1 part clean water to 5 parts paint.

Spray Recommendations

HVLP: Use a #5/2.2mm fluid set and dilute as required

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

* **Mouldshield** Fungicidal Eggshell from **Dulux Trade** contains: 3-iodo-2-propynyl-n-butyl carbamate.

Airless Spray: For broadwall surfaces use a standard tip e.g. 517. For more complex surfaces consider using a fine finish/low pressure tip for best results

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-4 hours.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/pp.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

This product contains max. 12g/l VOC. VOC content: Minimal (0-0.29%).



Issued 10/19

1011

Dulux Trade Evolve Matt

Use biocides safely. Always read the label and product information before use.

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Mouldshield, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2019.