

ULTRA GRIP PRIMER

Dulux Trade Ultra Grip Primer is a water-based two-pack primer, specially formulated to provide excellent adhesion for subsequent coats of paint, when applied to difficult substrates such as glazed ceramic wall tiles, laminates, glass, anodised aluminium, powder-coated steel and stove enamel surfaces. Suitable for interior and exterior use. Compatible with **Dulux Trade** paint systems.

KEY BENEFITS

- Two-Pack Primer
- For Stove Enamels, Laminates, Glass
- Excellent Adhesion on Problem Surfaces

PRODUCT INFORMATION

Typical Use

Suitable for use on interior and exterior use on difficult substrates.

Pack Size

0.8L Base and 0.2L Activator (1L when mixed).

Colour Range

Matt white.

Film Thickness

Film thickness will be dependent on the coverage achieved.

Wet: 100 microns.

Dry: 45 microns.

Composition (nominal)

Pigment: Non-lead pigments.

Binder: Epoxy resin.

Solvent: Water.

Volume Solids

45%.

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all loose or powdery material using a stiff fibre brush. Where necessary, thoroughly degrease, followed by rinsing with fresh, clean water.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Spot prime bare metal and metal fixings with 1 coat of **Metalshield** Zinc Phosphate Primer from **Dulux Trade**.

It is recommended that a small test area is applied before treating the entire surface to ensure compatibility.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Apply 1 coat of **Dulux Trade** Ultra Grip Primer, and then finish with an appropriate **Dulux Trade** paint system.

Mixing Ratio: supplied in correct proportions. Add all of the Activator to the Base container and mix thoroughly for at least 5 minutes, until the product is smooth and even. Do not mix part units. Badly activated or incorrectly mixed materials will affect performance and may cause early failure or discolouration.

Pot life: up to 6 hours at 20°C.

APPLICATION METHOD

Brush or short pile roller only. Do not spray.

As with all water based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 10m² per litre (at a dry film thickness of 45 microns).

Thinning

Ready to use when mixed. If required, add a maximum of 1 part clean water to 10 parts activated paint.

ULTRA GRIP PRIMER

Spray Recommendations

This product should not be sprayed.

Drying Times

Single coat at standard thickness:

Touch Dry: At 20°C – 4 -6 hours.

Recoat: Minimum of 16 hours and maximum of 7 days. Hard dry after 16 hours. Recoat before 7 days for optimum intercoat adhesion.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly. Find out more at duluxtrade.co.uk/pp.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/j): 140g/l (2010). This product contains max. 10g/l VOC. VOC content: Low (0.30-7.99%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 308) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Metalshield and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.