

# SHELLAC SANDING SEALER

## SHAKE / STIR WELL BEFORE USE

In colder weather or after prolonged storage the product may require stirring as well as shaking.

**Instructions for use:** Ensure all surfaces are clean, dry and free from grease and dust. Apply Shellac Sealer with a brush or cloth-often called a 'rubber'. Apply up to five coats, allowing to dry thoroughly between applications. After the first coat, the surface of the wood may appear roughened - lightly rub down with the finest wire wool or flour paper. The final coat can be applied using a mixture of 50/50 Methylated Spirit and Shellac Sealer. Clean all brushes etc with Methylated Spirit.

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Highly flammable liquid and vapour. • Causes serious eye irritation. • Keep out of reach of children. • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. • Wear protective gloves/protective clothing/eye protection/face protection. • Wash contaminated skin thoroughly after handling. • In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. • Store in a well-ventilated place. Keep cool. • Dispose of contents/container in accordance with national regulations.

Contains: Ethanol, Isopropanol, Butanone.




**Danger**

Very high: VOC content >50%  
VOCs (Volatile Organic Compounds) Contribute to  
atmospheric pollution.

EU limit value for this product (A/h 750 g/l (2007) 750 g/l (2010)  
This product contains max 614 g/l VOC

UN No. 1263



**2 Litre e**

**Barrettine**

St. Ivel Way, Warmley, Bristol BS30 8TY. T: +44 (0) 117 960 0060  
F: +44 (0) 117 935 2437 E: sales@barrettine.co.uk [www.barrettine.co.uk](http://www.barrettine.co.uk)