



WHITE KNOTTING

A quality 'clear' knotting made from White Shellac. For use on knots and resinous areas prior to painting/varnishing.

Reduces discolouration of topcoats when sealing knots under woodstains, varnishes and lighter coloured paints.

Suitable for use under solvent and waterbased paints.*

UFI: WX00-F081-0001-PF3V



250ml
UN No. 1263

Barrettine

SHAKE WELL For interior and exterior use

Instructions for use: Ensure all surfaces are sound, clean dry and free from any contaminants. Sand down thoroughly ready for priming and ensure all dust is removed. Wipe knots with Methylated Spirit prior to applying knotting. Apply one coat of knotting over and around all knots and resinous areas working well in, ensuring all knots are properly sealed. After a minimum of 30 minutes a second coat must be applied if subsequently finishing with a water based coating and recommended for solvent based coatings. Over coating possible after 1-2 hours. If knots are exuding excessive resin it is recommended to remove them and make good with wood filler.

***Caution:** We recommend doing a test area first to ensure compatibility with top coats/paint systems to be used.

HEALTH & SAFETY

- Highly flammable liquid and vapour. • Causes serious eye irritation.
- May cause damage to organs. • Keep out of reach of children. • If medical advice is needed, have product container or label at hand. • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. • IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Dispose of contents/container to national regulations.

Contains: Ethanol, Isopropanol, Butanone.

Very high: VOC content >50%

VOCs (Volatile Organic Compounds) Contribute to atmospheric pollution.

EU limit value for this product (A/h 750 g/l (2007) 750 g/l (2010)

This product contains max 614 g/l VOC



DANGER