

Truguard Fine Textured Masonry

A tough, water-based coating, suitable for most exterior masonry surfaces, with the benefit of masking slight surface imperfections. The durable film protects against weathering and atmospheric pollution, with anti-carbonation properties which resist the ingress of carbon dioxide from car exhaust fumes and prevent deterioration of concrete and steel.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Leyland's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.

Recommended uses

Interior Exterior

Type of substrate

Concrete, cement rendering, brick, stone, blockwork and pebbledash.

Colour availability

Brilliant White and Magnolia (5ltr).
Thousands of tinted colours also available (5ltr).

Finish

Matt

Volume solid

40%

Coverage

1 litre will cover approximately 8 square metres on smooth surfaces. In common with all wall paints, the spreading rate will be reduced on rough and absorbent surfaces such as pebbledash. When using more than one tin of a colour, it is advised that you intermix the quantity required beforehand.

Drying time

Recoat after 4-6 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

Film thickness

Wet: 143µm
Dry: 57µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Treat any mould or lichen with Sterilisation Wash as directed. Truguard Fine Textured Masonry can be applied directly over bare and previously painted surfaces provided these are clean, sound and firm. Chalky, underbound surfaces should be scraped, dry brushed and then given a coat of Truguard Stabilising Masonry Primer. Remove any limewash or distemper completely. Wear a suitable face mask when creating dust. Before applying Truguard Stabilising Masonry Primer to the whole surface, first carry out a test application to a small area. If this dries to a glossy film, thin with one part of Leyland White Spirit to two parts of Truguard Stabilising Masonry Primer and then test again in another small area. It is important to ensure that a non-glossy, dried, sealed surface is produced.

Application

Stir well before use. Do not thin, except for absorbent surfaces, when a small quantity of clean water may be added. Apply two full coats, allowing 4-6 hours between coats under normal drying conditions. Do not apply when air or surface temperatures are below 10°C, or when rain is imminent. Suitable for application by brush, roller and suitably adapted conventional spray.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- Do not breathe spray.
Wear respiratory protection.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354.