



Alkali Resisting Primer

DESCRIPTION

Johnstone's Trade Alkali Resisting Primer is a solvent based primer and sealer for interior and exterior use on, new or bare plaster, concrete, cement, render, or wood and metal surfaces. Used as a primer on unpainted surfaces, or sealer on powdery substrates it provides exceptional resistance to alkali attack.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Plaster, concrete, cement rendering, brick, stone and blockwork.

COLOUR RANGE

White.

FINISH

N/A.

VOLUME SOLID

57%

COVERAGE



Johnstone's Trade Alkali Resisting Primer will cover approximately 9-11 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 50µm, dry: 28µm.

DRYING TIME



Recoat after 16-24 hours under normal conditions.

TRANSPORTATION & STORAGE

STORE AWAY FROM HEAT AND FLAME.


To avoid the risk of spillage, always store and transport in a secure upright position.

CLEANER

Cleaner: White spirit.

VOC CONTENT

EU limit value for this product (Cat A/g): 350 g/l (2010) This product contains max 350 g/l VOC



KEY PROPERTIES

- Ideal for alkaline/chalking surfaces
- Binds powdery surfaces

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Avoid inhalation of dust, wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment Stir well before use. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

2.5 Litre, 5 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.