

## DESCRIPTION

Johnstone's Trade Anti-Slip Flortred is a single pack finish which is suitable for use on internal concrete, steel and wooden floors in light to medium traffic areas. It can also be used for exterior use to highlight walkways, car park spaces and other markings. Not suitable for use on large external areas. It provides a semi-gloss finish with a light aggregate for slip resistance. Tested to BS7976 Parts 1-3 for slip resistance, Johnstone's Trade Anti-Slip Flortred achieves a 'Low Slip Potential' classification according to the H.S.E. in both dry and wet conditions.

## RECOMMENDED USES



Light to medium traffic areas, where slip resistance is essential, eg. walkways, doorways, ramps & steps. For exterior use to highlight walkways, car park spaces and other markings. Not suitable for large external areas.

## SPECIAL PROPERTIES

Resistant to mild chemicals, water, oil and grease spillage. Slip resistant.

## COLOUR RANGE

Princess Grey, Dark Grey, Tile Red.

## FINISH

Semi-gloss.

## VOLUME SOLID

48%

## COVERAGE



Johnstone's Trade Anti-Slip Flortred Floor Paint will cover approximately 11 square metres per litre, depending on the nature and porosity of the surface. When using more than one tin of a colour in the same area, intermix before use.

## FILM THICKNESS

Wet: 90µm, dry: 40µm.

## DRYING TIME



Recoat after 16-24 hours under normal conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## THINNER

Cleaner: White Spirit.

## VOC CONTENT

EU limit value for this product (Cat A/i): 500 g/l (2010) This product contains max 500 g/l VOC



## KEY PROPERTIES

- Tested to BS7976 Parts 1-3 for slip resistance
- Suitable for interior and exterior use
- Semi-gloss finish with a light aggregate for slip resistance

## PREPARATION

All surfaces to be painted should be clean, dry and free from dust, laitance, loose or flaking material. New concrete or cement should be allowed to mature for several months before painting. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure maximum ventilation during application and drying. When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. Stir well before use. Apply by brush or roller which should be fully loaded for best results. Apply paint evenly by brush and avoid overspreading. To ease application, the first coat may be thinned with up to 5% by volume of White Spirit. Allow to dry overnight before applying a second coat, if required.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZE

5 Litre.