



# Joncryl Water Based Primer Undercoat



## DESCRIPTION

Johnstone's Trade Joncryl Water Based Primer Undercoat is a high quality, acrylic resin based combined primer and undercoat formulated for interior use on wood, plaster, hardboard, cement and brickwork. It provides a low odour, quick drying, high opacity alternative to solventborne primer and undercoats. Can also be used externally.

## RECOMMENDED USES



Suitable for interior and exterior use.

## TYPE OF SUBSTRATE

Wood, plaster, concrete, cement rendering, brickwork and blockwork.

## COLOUR RANGE

Brilliant White

## FINISH

Not applicable.

## VOLUME SOLID

32%

## COVERAGE



Johnstone's Trade Joncryl Water Based Primer Undercoat will cover approximately 12-14 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 77µm, dry: 24µm.

## DRYING TIME



Touch dry in 1 hour. Recoatable after 1-2 hours. High humidity and low temperatures will prolong drying times.

## TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

## THINNER

Thinner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010) This product contains max 3g/l VOC



## KEY PROPERTIES

- Superb obliteration and covering power
- Low odour and quick drying

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down bare timber surfaces with dry glasspaper to remove raised grain and sharp edges. Apply Johnstone's Trade Woodworks Knotting Solution to knots and resinous surfaces. Prime bare metal surfaces with the appropriate Johnstone's Trade primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir thoroughly before use. Easy to apply by brush or roller. Also suitable for application by spray. Apply liberally, brushing firmly into the surface. Do not apply when the air or surface temperature is below 10°C or externally when rain is imminent.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

1 Litre, 2.5 Litre, 5 Litre.



For more information on our products and services call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).