



Stormshield Pliolite® Based Masonry

DESCRIPTION

Johnstone's Trade Stormshield Pliolite® Based Masonry is a solventborne paint for exterior use on cement rendering, rough cast, brick and concrete. It provides a premium quality, smooth matt finish with excellent adhesion to previously painted and porous surfaces. The smooth, durable coating can be applied in extreme temperatures as low as -5°C and is showerproof within 20 minutes, enabling all year round application.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Tintable to a range of colours available in Voice of Colour exterior colours.

FINISH

Matt.

VOLUME SOLID

33%

COVERAGE



Johnstone's Trade Stormshield Pliolite Based Masonry Finish will cover approximately 6-10 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 125µm, dry: 41µm.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 16-24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME**

® Pliolite is a registered Trademark of the OMNOVA.

CLEANER

Thinner: White spirit.

VOC CONTENT

EU Limit Value for this product (Cat A/c): 430g/l (2010) This product contains max 430 g/l VOC



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.

KEY PROPERTIES

- Showerproof in 20 minutes
- Applies at -5°C
- 15* YEARS LIFE EXPECTANCY

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Sterilisation Wash as directed. For further advice contact Technical Advisory, on 01924 354354.

*15 YEARS EXPECTED LIFE

Johnstone's Trade Stormshield Pliolite® Based Masonry provides protection for up to 15 years, provided it has been applied according to the instructions, onto properly prepared surfaces.

APPLICATION



Ensure maximum ventilation during application and drying. Stir well. Easy to apply by brush or roller. Seal absorbent surfaces with a coat of Johnstone's Trade Stormshield Stabilising Solution as directed. If more than one can of a colour is to be used in the same area, intermix before use.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.