

Barrettine
TRUSTED BY THE PROFESSIONALS

CREO SOLVE®

FOR EXTERIOR USE ONLY

DARK BROWN
OIL BASED TIMBER TREATMENT



UFI: VH30-MQXX-500V-HPKT



5 015861 006349

4 Litre e

Colour may vary from pack to pack. Match before use.
Image shown is a guide only and final appearance may vary depending on timber type & condition.
Carry out a test area first to make sure you are happy with the finish.

CREOSOLVE® DARK BROWN

**SHAKE BEFORE USE &
AGITATE DURING USE**

APPLICATION

Barrettine CreoSolve® is a lower hazard alternative to traditional Creosote and some other Creosote replacement wood treatments. Similar physical/water repellence/application characteristics of traditional Creosote but contains no biocide. An oil based, bitumen and wax treatment for the protection of exterior timbers such as fence panels & fence posts etc. (Not suitable for decking or exterior wooden furniture). Apply by brush at a rate of 1 litre product per 6-8m² of surface or by dipping timber for 20 minutes.

EXTERIOR USE ONLY:

ABOVE GROUND APPLICATION

DIRECTIONS FOR USE

Wear appropriate personal protective equipment (PPE) such as chemical resistant gloves, overalls and eye/face protection to protect against splashes. If in doubt speak, to your PPE supplier and show them this label/product, or call us for further advice. Do not dilute. Ensure surfaces to be treated are clean, dry and free from surface coatings such as paint, varnish etc. Remove all deposits of mould, lichen or algae from timber surfaces using a stiff brush. Apply by brush or dipping only. Wash brushes and tools with white spirit. As the shade may vary from batch to batch, it is recommended that test patches are applied before general application.

Note: If using several containers recommend to mix before use to ensure colour uniformity.

Barrettine

Barrettine Products

St. Ivel Way, Warmley, Bristol, BS30 8TY.

T: +44 (0) 117 960 0060 E: sales@barrettine.co.uk

www.barrettinePro.co.uk

Group website: www.barrettine.co.uk

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION



Contains: Kerosine (petroleum)

Warning

Flammable liquid and vapour.

Causes skin irritation. May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours, spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection. Avoid release to the environment. Dispose of contents, container to a hazardous or special waste collection point.

VOC. The EU Limit for this product Cat E is 400 g/l

This product contains max 400 g/l

Barrettine (Europe) Ltd

Unit 3D North Point House,

North Point Business Park,

New Mallow Road, Cork. T23 AT2P. Ireland

T: +44 (0) 117 9600060

4 litre e

Barrettine
TRUSTED BY THE PROFESSIONALS

CREO SOLVE®

FOR EXTERIOR USE ONLY

LIGHT BROWN
OIL BASED TIMBER TREATMENT



UFI: VH30-MOXX-500V-HPKT



4 Litre e

Colour may vary from pack to pack. Match before use.
Image shown is a guide only and final appearance may vary depending on timber type & condition.
Carry out a test area first to make sure you are happy with the finish.

CREOSOLVE® LIGHT BROWN

**SHAKE BEFORE USE &
AGITATE DURING USE**

APPLICATION

Barrettine CreoSolve® is a lower hazard alternative to traditional Creosote and some other Creosote replacement wood treatments. Similar physical/water repellence/application characteristics of traditional Creosote but contains no biocide. An oil based, bitumen and wax treatment for the protection of exterior timbers such as fence panels & fence posts etc. (Not suitable for decking or exterior wooden furniture). Apply by brush at a rate of 1 litre product per 6-8m² of surface or by dipping timber for 20 minutes.

EXTERIOR USE ONLY:

ABOVE GROUND APPLICATION

DIRECTIONS FOR USE

Wear appropriate personal protective equipment (PPE) such as chemical resistant gloves, overalls and eye/face protection to protect against splashes. If in doubt speak, to your PPE supplier and show them this label/product, or call us for further advice. Do not dilute. Ensure surfaces to be treated are clean, dry and free from surface coatings such as paint, varnish etc. Remove all deposits of mould, lichen or algae from timber surfaces using a stiff brush. Apply by brush or dipping only. Wash brushes and tools with white spirit. As the shade may vary from batch to batch, it is recommended that test patches are applied before general application.

Note: If using several containers recommend to mix before use to ensure colour uniformity.

Barrettine

Barrettine Products

St. Ivel Way, Warmley, Bristol, BS30 8TY.

T: +44 (0) 117 960 0060 E: sales@barrettine.co.uk

www.barrettinePro.co.uk

Group website: www.barrettine.co.uk

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION



Contains: Kerosine (petroleum)

Warning

Flammable liquid and vapour.

Causes skin irritation. May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours, spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection. Avoid release to the environment. Dispose of contents, container to a hazardous or special waste collection point.

VOC. The EU Limit for this product Cat E is 400 g/l

This product contains max 400 g/l

Barrettine (Europe) Ltd

Unit 3D North Point House,

North Point Business Park,

New Mallow Road, Cork. T23 AT2P. Ireland

T: +44 (0) 117 9600060

4 litre e