



THE ORIGINAL  
**MORRIS & Co**

LOVINGLY CRAFTED SINCE 1861

**PAINT**

**CHALKY MATT EMULSION**

**CHARACTER**

Gorgeously flat and with a great depth of colour, Chalky Matt Emulsion from Morris & Co. Paint offers the perfect heritage hue with each brushstroke. Made with only premium ingredients that are planet-friendly, Chalky Matt's wipeable finish leaves an enduringly harmonious look.

Made for the modern craftsman with colours sourced from the Morris & Co. archive, Chalky Matt is ideal for enveloping walls and ceilings in a timeless Morris & Co. palette.

**LOOK FORWARD TO**

- Minimal drying time of just two hours
- Strong scrub resistance, perfect for busy homes
- Reduced residual brush marks and cutting in, leaving an unblemished heritage look

**PREPARATION**

Ensure good ventilation during application and drying. All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime base surfaces with an appropriate primer. Rub down previously glossed painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces as they may contain harmful lead. Prime base surfaces with an appropriate primer.

**APPLICATION**

Stir well before use and apply by brush or roller. Apply 2 coats. Additional coats may be required on new plaster or where a larger colour change is desired. Do not apply in temperatures below 10°C or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

**CLEANING**

Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

**HEALTH & SAFETY**

- Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.

- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or white spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell. Safety data sheet available on request.

**RECOMMENDED USES**

Suitable for commercial and residential spaces.

**TYPE OF SUBSTRATE**

Interior walls and ceilings.

**COLOUR RANGE**

Morris & Co. Paint

**FINISH**

Minimal sheen.

**VOLUME SOLID**

35%

**COVERAGE**

Approximately 15 square metres per litre depending on the nature and porosity of the surface.

**DRYING TIME**

Recoat after 2 - 4 hours.

**TRANSPORTATION & STORAGE**

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

**CLEANER**

Clean water.

**VOC CONTENT**

- Minimal VOC Content <0.29%
- VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.
- EU limit value for this product (Cat A/a): 30g/l (2010).
- This product contains max 2g/l VOC.

**FILM THICKNESS**

Wet: 100µm, Dry: 48µm

**SIZES**

2.5 Litre, 5 Litre