



THE ORIGINAL
MORRIS & Co

LOVINGLY CRAFTED SINCE 1861

PAINT

WATER-BASED ACRYLIC EGGSHELL

CHARACTER

Our Water-Based Acrylic Eggshell is highly opaque with a low sheen, introducing an irresistibly rich finish to interior spaces. With colours sourced from the Morris & Co. design archive, we've created this authentic palette for the modern craftsperson.

Bring a sophisticated heritage look to interior walls, ceilings, wood and metal work. With low odour and a quick-drying finish that is resistant to condensation and yellowing, this versatile paint is also suitable for use in kitchens, bathrooms, hallways, conservatories and exterior woodwork such as doors and window frames.

LOOK FORWARD TO

- Irresistibly smooth finish with high opacity
- Hardy, scrub resistant surface tailor made for busy homes
- Low-odour, quick drying, yellowing and condensation-resistant application
- Water-based recipe and planet-friendly ingredients

PREPARATION

Ensure good ventilation during application and drying. All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime base surfaces with an appropriate primer. Rub down previously glossed painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces as they may contain harmful lead. Prime base surfaces with an appropriate primer.

APPLICATION

Apply 2 coats. Additional coats may be required on new plaster or where a larger colour change is desired. Do not apply in temperatures below 10°C or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

CLEANING

Remove as much product as possible from application equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

HEALTH & SAFETY

- Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.

- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or white spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell. Safety data sheet available on request.

RECOMMENDED USES

Suitable for commercial and residential spaces.

TYPE OF SUBSTRATE

Interior walls and ceilings, prepared wood and primed metal.

COLOUR RANGE

Morris & Co. Paint

FINISH

Low sheen.

VOLUME SOLID

36%

COVERAGE

Approximately 12 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME

Recoat after 2 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

Clean water.

VOC CONTENT

- Low VOC Content 0.3-7.99%
- VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.
- EU limit value for this product (Cat A/d): 130g/l (2010).
- This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 83µm, Dry: 30µm

SIZES

1 Litre, 2.5 Litre